

Flex-Air Fittings

The Flex-Air Fitting is designed to rotate 360° at up to a 75° angle. The Flex-Air Fitting helps to alleviate Carpal Tunnel Syndrome and other stress related injuries in the workplace.

 Unique design provides free 360° rotation with up to a 75° angle of rotation in any direction

TUTHILL Coupling Group

R

- Many styles and sizes available
- 145 psig (10 Bar) pressure rating (all models)
- Provides flexibility of tool position to help alleviate Carpal Tunnel Syndrome and back stress resulting in fewer lost-time injuries
- Minimizes paint damage
- Prevents kinking of air supply hose

- Assembly air lines in
- automotive, electronic and other industries
- Mechanical joints
 for robotics
- Vibration isolation
- Commercial and residential construction

- Integrated steel/ polyurethane construction
- Steel balls
- Buna-N (Nitrile) seals
- Thread sealant standard on male NPTs

Flex-Air Fittings



Female to Male		
Part Number	FA25F-25M	
Inside Dia.	0.2" (5 mm)	
Connectors	1/4" NPT Female	
	1/4" NPT Male	
Part Number	FA25F-37M	
Inside Dia.	0.3" (7.5 mm)	
Connectors	1/4" NPT Female	
	3/8" NPT Male	
Part Number	FA37F-37M	
Inside Dia.	0.3" (7.5 mm)	
Connectors	3/8" NPT Female	
	3/8" NPT Male	

3/8" NPT Male

	Male to Male	
Part Number	FA25M-25M	
Inside Dia.	0.2" (5 mm)	
Connectors	1/4" NPT Male	
	1/4" NPT Male	
Part Number	FA37M-37M	
Inside Dia.	0.3" (7.5 mm)	
Connectors	3/8" NPT Male	
	3/8" NPT Male	





FA25AR-25M
0.2" (5 mm)
ARO 210 Interchange
1/4" NPT Male









TUTHILL | Hansen Couplings Coupling Group | Coupleurs Gromelle 1000 West Bagley Road, P.O. Box 805 Berea, Ohio USA 44017-0805 Tel 440 826-1115 Fax 440 826-0115 www.tuthill.com

