# Series P-30 & P-40 Industrial Interchange





**Industrial Interchange Plastic Quick Connect Couplings** designed for compressed air. Body sizes are 1/4" and 3/8".

## **Features**

- · Plastic socket body and plug
- Light-weight
- · Less likely to damage painted or easily dented surfaces than metal couplings
- · Easy, automatic, push-to-connect design provides instantaneous connection and disconnection of lines, plus automatic shut-off of socket end of line
- 1/4" socket accepts MIL-C-4109 plugs

## **Standard Materials**

- Socket
  - Acetal Body
  - Polypropylene Sleeve
  - Zinc Plated Steel Valve
- Buna-N (Nitrile) Seal
- Stainless Steel Springs
- Plug
  - Acetal
  - Series P-30 accepts all Series 3000 plugs
  - Series P-40 accepts all Series 4000 plugs

# **Rated Pressure**


Series	Size	PSI	BAR
P-30	1/4"	150	10
P-40	3/8"	150	10

<sup>\*</sup> At temperatures up to 125°

# **Flow Capacity**

Series	†Ac
P-30	28
P-40	45

+ Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure




AIR-FLOW, scfm (100 psig Inlet Pressure)

#### Plugs **Sockets**

		Dimen	Dimensions	
Part No.	Hose I.D.	Α	В	
P4-30S-25H P7-40S-37H	1/4" 3/8"	2.66 2.82	1.25 1.44	

**Hose Stem End Connections** 



c	ł
	D
Hex_	1

		Thread		Dimensions		
	Part No.	Size	С	D	HEX	
)	P4-30P-25M P7-40P-37M	1/4-18 NPTF 3/8-18 NPTF				

**Male End Connections**